



1000111010101100100011110001000001111000100

digital perfection

NEW



ESC/POS Thermal Printer

EP-2000





1000111010101100100011110001000001111000100

digital perfection



Specification

EP-2000

Printing Method	Line Thermal Dot Printing
Print width	72 mm paper / 576 dots
Dot Density	8 x 8 dots/mm (203dpi x 203 dpi)
Print Speed	Max 220 mm/sec (1760 dots line/sec)
Characters per line	Font A - C: 48 characters/line, 36 columns, 12 x 24 Font B - D: 64 characters/line, 48 columns, 9 x 16
Recommended paper	Thermal paper Roll: 80 mm or 58 mm / Ø to max 102 mm, thickness 65-85 µm
Paper Loading	Easy paper lading method
Reliability	Printer head life: 150 km printed paper Auto cutter life: 2 million pulses
Interfaces	<ul style="list-style-type: none">• RS 232C• USB - type v. 1.1• LAN – 100 Mbps(100BASE-TX)
Emulation	ESC/POS Linear Barcode: EAN 8, EAN 13, UPC-A, UPC-E, Codabar, Code 39, Code 128 2-Dimensional: PDF 417, QR code
Power Supply	Input: ~100 - 240V, 50/60Hz
Input Buffer	36 864 b (Option 131 072b)
Weight, kg	2.000
Dimension (W) x (D) x (H) mm	147 x 207 x 147
Environment	<ul style="list-style-type: none">- Operating temperature +5P° to +40°C- Operating humidity 35 to 85% RH (Free of dew condensation)- Storage temperature -20°C to +60°C- Storage humidity 10 to 90% RH (Free of dew condensation)



DATECS

115 A Tsarigradsko shosse Blvd., Sofia 1784, BULGARIA
tel: +359 (2) 974 00 55; fax: +359 (2) 974 11 00; e-mail: sales@datecs.bg; www.datecs.bg

