

CHECKOUT SCALES

KS-400 series



KS-400S with optional
Honeywell Stratos
MK2400 scanner
(scanner not included)



Dimensions
DATA IN mm

A 420



Characteristics and functionality

Main characteristics

- Weighing kit to integrate with scanner for checkout applications.
- The display shows: weight only or weigh-price-total.
- The rotatory display allows an appropriate reading.
- Modular and modern design.
- Easy integration into counters.
- ECR/POS connection.
- Optional scanner (not included).
- Valid for legal metrology (connected to POS / ECR).

Features

- EAN heading programming (according to the communication protocol).
- Tare, fix tare and manual zero.
- Display of price in a secondary currency.
- Energy saving via programmable on and off back lighting switching and automatic disconnection.
- Power supply and communications through one single USB cable (only for KS-400 M, and depending on the scanner).
- The weighing components are located in an isolated area, so scanner maintenance operations may be carried out without the need to unseal the equipment.

Models

for Honeywell Stratos MK2421 scanner*

for Datalogic Magellan scanners*

for Zebra scanners*

Honeywell	Buyer display	Scanner communication	DATALOGIC	Buyer display	Compatible scanner models*	ZEBRA	Vendor display	Customer display	Compatible scanner models*
KS-400 S-1 DISP.	-	1 cable	KS-400 M-1 DISP.	-	8300 / 8400 / 9300i / 9400i	KS-400 Z-0 DISP.	POS disp.	-	MP7000
KS-400 S-1 DISP.	-	2 cables	KS-400 M-2 DISP.	LCD Graph	8300 / 8400 / 9300i / 9400i	KS-400 Z-1 DISP.	LCD Graph	-	MP7000
KS-400 S-2 DISP.	LCD Graph	1 cable	KS-400 M-1 DISP.	-	9800i	KS-400 Z-2 DISP.	LCD Graph	LCD Graph	MP7000
KS-400 S-2 DISP.	LCD Graph	2 cables	KS-400 M-2 DISP.	LCD Graph	9800i				

* Scanner not included.

Capacity/Accuracy 6 kg/2g - 15 kg/5g

Displays

- LCD matrix graphic backlit displays (1 or 2 depending on the model).
- Show: only weight or weight – price / kg – total price (connected to a POS and according to the communication protocol).

Communication to PC / POS / ECR

- RS-232 interface.
- USB (only in KS-400M, and depending on the scanner).
- Communication protocols available for the main POS and ECR in the market.
- Multi-protocol: the communication protocol is selected in the weighing kit among the available ones, previously recorded in the weighing kit.
- Upgradeable software from PC.

Compatibility with scanners

- Honeywell Stratos MK2421 scanners (communication by one or two cables).
- Datalogic Magellan 8300 / 8400 / 9300i / 9400i / 9800i scanners.

Power supply

- Mains: through the scanner (5 or 12 V).
- Others: through USB cable 5 V (PC, etc.). Only in KS-400 depending on the scanner.