



500 Range





500 RANGE retail scales bring a new concept in technology and ease of operation. With **4 SERIES** of products, featuring different levels of functionality: **WIND, MISTRAL, TORNADO and STAR.**

Features

- Extensive information for each PLU: normal price and offer price, price for weight ranges and by kg/100 g, up to 3 names of 20 characters or 2 names of 30 characters, up to 20 free texts of 24 characters, 1 text of 3,000 characters, etc.
- PLU search by code or name.
- Preset keys to programming menus: to change prices, register PLUs or vendors, etc.
- Direct access to 999 PLUs from the keyboard.
- Drill down menus.
- Printing of the scale menus.
- Programmable macros: recording of a sequence of keys to create direct access to any task (reopening of receipt, lists, change in batch number, etc.).
- Sales and management reports: sales (by article, vendor, time frames, last month, etc.), margins, balance available in the cash drawer, modified PLUs, etc.
- Fast and reliable communication between scales, with PC and mobile devices (via DWS).
- Stocks management on the scale.
- Stock / order mode.

Capacity / Accuracy

- Mono-range (3.000 divisions): 15 kg / 5 g.
- Optional:
- > Mono-range (3.000 divisions): 30 kg / 10 g.
- > Multi-range (3.000 divisions): 6 kg / 2 g 15 kg / 5 g, o 15 kg / 5 g - 30 kg / 10 g.
- \rightarrow Mono-range (6.000 divisions): 12 kg / 2 g o 30 kg / 5 g.

Construction

- Highly resistant ABS plastic or stainless steel casing.
- Stainless steel plate.
- Access to all non-metrological components without the need to unseal the scale (except in Wind Series).





Models and formats (Dimensions)

Displays

- Backlit LCD segment display (W150.2 x H43.4 mm) for vendor and buyer (showing weight, price/ kg, total, tare, vendors and name of article).
- Optional:
- > LCD matrix graphic display (W134 x H41 mm or W188 x H55 mm) for vendor and buyer. Possibility of showing: logos, profitability codes, warning messages sent from a PC (on vendor display) and advertising messages with animated effects on buyer display.
- > 7" TFT display for vendor and buyer (shows advertising and promotional images even during sales operations). Available in Star Series.








Segment display

Graphic display L size




Graphic display L size



7" TFT colour display

Printer(s)

- Models available with 1 printer for receipts, 1 printer for labels (also suitable for receipts by changing the paper roll and the working mode) or 2 printers (for receipts and for labels)
- 54 mm thermal printer.
- High resolution (8 dots/mm) and speed (depending on models, up to 100 mm/sec).
- Cassette for immediate paper roll change (in label printers).
- Optional:
- > Linerless, in label printers (except for Wind Series).



Receipts

- 15 fonts (6 monospaced + 9 multispaced: more modern and legible).
- Up to 70 lines, depending on Series.
- EAN-13 bar codes. In addition, EAN-128 and CODE-128 in Tornado and Star Series.
- 9 payment methods.
- Total in National currency and another 3 currencies.
- Discounts per line and total.
- 2 fixed formats and up to 2 programmable formats.
- 4 logos per receipt.
- Name of vendor.
- Customers on account.
- Loyalty points, in Tornado and Star Series.
- Recipes, in Tornado and Star Series.

Labels


- 15 fonts (6 monospaced + 9 multispaced: more modern and legible).
- From W30 x L30 mm up to W60 x L150 mm, depending on models.
- 20 fixed formats and up to 40 programmable formats.
- 100 logos.
- EAN-13 bar codes. In addition, EAN-128 and CODE-128 in Tornado and Star Series.
- Up to 60 fields of information.
- 100 programmable texts.
- Manual and automatic pre-packing modes.
- 3 levels of totals.
- Printing of "n" copies of labels.
- Printing with 90°, 180° and 270° rotation
- Automatic adjustment of the paper detection option.
- Packaging date, expiry date and extra date (for any application).
- Alphanumeric batch number.
- Up to 10 types of generic traceability (for meat, fish, fruit, vegetables, etc.) up to 99 products. Included in the prevailing European legislation on bovine traceability.

Food information

- Compliance with EU Regulation 1169/2011 on the provision of food information to consumers as of 13 December 2016:
- > Minimum letter size: 1.2 mm.
- > Effect (bold, underlined or both) for each character in the text, depending on models.
- > Possibility of using the general text "G" (3,000 characters) for ingredients, in lower case or UPPER CASE to highlight allergens.
- > Possibility of including a table of nutritional facts.
- > Free texts (20 x 24 characters).*
- > For direct sale receipts and labels: possibility of indicating in the PLU name (with an * or other symbol) those that contain allergens and programming a text, such as "* Consult allergens".
- Depending on models, possibility of printing 2 labels for each operation: programmable by PLU, configurable information, 2nd automatic or manual label (also to be used as promotional labels).

Elchenstzaße 4, 12435 Daytime patisserie, 30 Number: AdB172	Sarlin Ltd.	
Store No: 2301 POS No: 002	ified invoice	Markelabour
ATTENDED BY: AN	.XZ	BLACK FOREST GATEAU
UNIT DESCRIPT,	PRICE TOTAL	Lacteal ingredients (ALLERSES): (BUTTRANILE, ski) HILE, refined and fully hydrogenated vegetable far
1 CHOCO CROISSANT 1 SELF-RISING FLOUR 1 NINI DANISH 1 CLASSIC NUFFIN 1 ALL BUTTER CROISSAN 2 MAPLE AND FECAN PLA 1 TRIPLE CHOCO COOKIE Tay basa	2,05 2,05 2,05 2,05 2,05	apin terme ind pain <u>index</u> , witterstring, studies, and the set of the set
Tax base VAT 10%	17,65 1,77	9-471, studilizers (2-412 and 1-415), gelling ag- 12-451 and 2-50011, soit and conservative (2-70) Becoard in inspecience. Automatic the conservative (2-70) Issues, opposite, coord Butter, anhydrous <u>VIIE</u> second vanila arona, emilisiter (<u>20</u> Jecithin, matural vanila).
TOTAL Euro	19,42	Contains <u>GLUTEN, ECG. HILF, BV</u> and may contain <u>W</u> <u>HEANTER</u> and <u>BULFITES</u> .
CREDIT CARD	19,4Z	Nutritional Facts
2-500006-0194	26	Esergetic value 1356 kj / 324 k Jata –
VAT Include	1	Distary fiber Proteins 3, Sait 9,1
THANK YOU FOR C		Salt 0,1 Bow TO definat: Fridge: SE: Noot temperature: SE.
Give us your opi		Store balow 15 ° C. Once thereo, keep refriberated between 0 C and 5 ° S.
		Elberteini 0 Class 3 Clas 3 Class 3 <thclass 3<="" th=""></thclass>
	の変	Price 9,75 €

* Note: Labels of basic models of Wind Series (W-010, W-010 B, W-015) and Mistral Series (M-510, M-510 B, M-515) do not comply with the labeling of packaged food Regulation (only 5 texts of 24 characters are available).



500 RANGE

Table of models

OPT. = Optional. * Using Shift and Vendor keys. ** Only in Double body and Self-service format. *** Except for Hanging ABS format												ormat.										
Series	Model Format			Di	spl	ay		PLUs			Printer					uni- Batte						
	B) (HS)												ner	ion	Ca	ns 						
			Double Body (DB) Hanging ABS (HA)	Hanging St. Steel (HS) Self-service (SS)	Segment LCD	Graphic LCD L Graphic LCD XL	7" Colour TFT	Total	Direct	Macros	Vendors	Paper type	Speed (mm/s)	Linerless	Linerless Built-in scanner	Interconnection	Ethernet WiFi	Scanner	Cash drawer	acu	High capacity	Anti-BlackOut
	W-010	• •			•			2.000	45x2+4x2*		5	Receipt	80			5	• 0P	•	•			OPT.
	W-010 B	• •			•			2.000	45x2+4x2*		5	Receipt	60			5	• 0P		•		•	
Wind	W-015	• •			٠			2.000	45x2+4x2*		5	Label (or Receipt)	80			5	• 0P		•			OPT.
Ň	W-020	• •			• ()PT.		5.000	40x2+9x2*	2	10	Receipt	100			10	• 0P	. •	•			OPT.
	W-020 B	••			• ()PT.		5.000	40x2+9x2*	2	10	Receipt	60			10	• 0P	. •	•		•	
	W-025	••			• ()PT.		5.000	40x2+9x2*	2	10	Label (or Receipt)	100			10	• 0P	. •	•			OPT.
	M-510	• •	• •	•	•			2.000	45x2+4x2*		5	Receipt	80		OPT.**	5	• 0P		•		C)PT.***
	M-510 B	• •	•		•			2.000	45x2+4x2*		5	Receipt	60		OPT.**	5	• 0P		•		•	
a	M-515	• •	• •	•	٠			2.000	45x2+4x2*		5	Label (or Receipt)	80		OPT.**	5	• 0P		•		C)PT.***
str	M-520	• •	• •	•	• ()PT.		5.000	40x2 + 9x2* (F, P) 70x2 + 9x2* (DB, HA, HS)	2	10	Receipt	100		OPT.**	10	• 0P	. •	•		()PT.***
Mistral	M-520 B	• •	•		• ()PT.		5.000	40x2 + 9x2* (F, P) 70x2 + 9x2* (DB)	2	10	Receipt	60		0PT.**	10	• 0P	. •	•		•	
	M-525	• •	• •	• •	• • ()PT.		5.000	40x2 + 9x2* (F) 70x2 + 9x2* (P, DB, HA, HS) 100 (SS)	2	10	Label (or Receipt) (only Label in Self-Service)	100	OPT.	OPT.**	10	• 0P	•	•		C)PT.***
0	T-530		• •	•	• ()PT. OP ⁻	T.	8.000	60x2+19x2*	5	20	Receipt	100		0PT.**	16	• 0P		• 0F	PT.	C)PT.***
g	T-530 B		•		• ()PT. OP ⁻	T.	8.000	60x2+19x2*	5	20	Receipt	60		0PT.**	16	• 0P	. •	• 01	PT.	•	
Tornado	T-535	• •	• •	••	• • ()PT. 0P ⁻	T.	8.000	30x2 + 19x2* (F) 60x2 + 19x2* (HA, HS) 90x2 + 19x2* (P) 95x2 + 19x2* (DB) 100-150-208 (SS)	5	20	Label (or Receipt) (only Label in Self-Service)	100	OPT.	OPT.**	16	• 0P	. •	• OF	PT.	()PT.***
	S-540		• •	•	• ()PT. OP ⁻	T.	10.000	60x2+19x2*	60	20	Receipt	100		0PT.**	16	• 0P		•		()PT.***
	S-540 B		•		• ()PT. OP	T.	10.000	60x2+19x2*	60	20	Receipt	60		0PT.**	16	• 0P		• (•	•	
	S-540 COLOUR		•	•			•	10.000	60x2+19x2*	60	20	Receipt	100		OPT.**	16	• 0P	. •	•			OPT.
Star	S-545	• •	••	••	• • ()PT. OP'	T.	10.000	$\begin{array}{c} 30x2+19x2^{*}\text{(F)}\\ 60x2+19x2^{*}\text{(HA, HS)}\\ 90x2+19x2^{*}\text{(P)}\\ 95x2+19x2^{*}\text{(DB)}\\ 100-150-208\text{(SS)} \end{array}$	30 (F) 60 (HA, HS) 90 (P) 95 (DB) 100 (SS)	20	Label (or Receipt) (only Label in Self-Service)	100	OPT.	OPT.**	16	• OP	. •	• (•	()PT.***
	S-545 COLOUR	•	•	•			•	10.000	60x2 + 19x2* (HS) 90x2 + 19x2* (P) 95x2 + 19x2* (DB)	60 (HS) 90 (P) 95 (DB)	20	Label (or Receipt)	100	OPT.	OPT.**	10	• 0P	•	•	•		OPT.
	S-547		• •	•	• ()PT. OP ⁻	T.	10.000	60x2+19x2*	60	20	Receipt + Label	100	OPT.	OPT.**	16	• 0P	. •	•	•	()PT.***
	S-547 COLOUR		•	•			•	10.000	60x2+19x2*	60	20	Receipt + Label	100	OPT.	OPT.**	16	• 0P		• •	•		OPT.
			Double Body (DB) Hanging ABS (HA)	Ha		Graphic LCD L Graphic LCD XI.		Total	Direct	Macros	Vendors	Paper type	Speed (mm/s)	Linerless	Built-in scanner	Interconnection		Sca	Cash dri nui	_		Anti-BlackOut
Series	Model	F	orm	at	Di	spl	ay	OPT	PLUs	nd Verster	01/2	Printe:		Self.		for		atio			Batte	
								0PT. =	Optional. * Using Shift a	na Vendor k	eys.	Only in Double bod	y and	Self-s	service	tormat	*** E	xcept	ior Ha	angin	g ABS f	ormat.



Communications

- TCP/IP Ethernet for interconnection and connection to PC.
- RS-232, for connection to scanner.
 (Not available in basic models of Wind Series, W-010, W-010 B, W-015, and Mistral Series, M-510, M-510 B, M-515).
- USB: Included in Star Series; optional in Tornado Series.
- Wi-Fi optional.

Built-in scanner (optional)

- Available the option of built-in scanner in 500 Range scales of Double body and Self-service formats.
- Functions of built-in scanner:
- > Search a product by its EAN-13 or EAN-8 (only one EAN per product).
- > Pre-packed products: read information like weight/quantity/ price contained in the barcode.

Security

• Access to different protected programming menus via configurable passwords.

Interconnection

• Up to 16 scales per section.

Connectivity with other devices

- PC.
- Bar code scanner (powered by the scale 5 VDC) to read EAN-13 and EAN-128 bar codes. In addition, EAN-128 in Tornado and Star Series.

(Not available in basic models of Wind Series, W-010, W-010 B, W-015, and Mistral Series, M-510, M-510 B, M-515).

Power supply

- Mains: 110 up to 230 VDC.
- Depending on model, also:
- > High performance rechargeable internal battery: up to 52 hours of life (calculated for 1,500 receipts, with 3 articles per receipt) and connector to external battery 12 V.
- > Anti-blackout rechargeable internal battery 24 V and connector to external battery 24 V.

PC Software

- DFS (Dibal Friendly Software):
- > Programming of scales.
- > Receipt of sales data.
- > Data backup copy.
- > Graphic design of receipts and labels.
- Design and management of advertising images for graphic display and colour TFT.
- DLD (Dibal Label Designer):
- > Graphic design of receipts and labels.
- Integration tools:
- In Windows or Linux to facilitate communication with the Back-Office.

Scale firmware

- DWS (Dibal Web Server):
- > Allows access to the information on each scale (via passwords) from any computer or mobile device with an Internet browser.



Specifications and images subject to change without prior notice - Ref.: 1080411 - Brochure 500 Range v 2.0